



Head Stud Kit PART# - RK10085-HSK

APPLICATION(S): Kawasaki 1.5L & 1.6L Engines

Required tools OEM Service Manual Part# CALL

*** NOTE: Allow craft's engine to cool thoroughly before performing installation. ***

- INSTALLATION INSTRUCTIONS -

- 1. To ensure proper thread engagement and accurate torque readings clean ALL threads in block. Chase if necessary.
- 2. Clean and inspect all hardware prior to installation. Look for obvious defects or shipping damage.
- 3. Check all hardware for proper fit, length, and dimension prior to installing.
- 4. Coat threads on both ends of stud with motor oil.
- 5. Screw studs (coarse threaded end) into block. NOTE: Torque studs to 12~15 ft·lbs.
- 6. Remove excess oil from block. Install cylinder head onto studs following service manual. Check for binding or misalignment.
- 7. Install supplied nuts onto studs and screw hand tight. NOTE: Do not use washers.
- 8. Following torque sequence outlined in service manual torque nuts to 36~42 ft•lbs.

CYLINDER HEAD GASKET: DO NOT reuse the original head gasket. A new OEM cylinder head gasket can be used. However, for modified engines we strongly recommend using a new RIVA Pro-Series Cylinder Head Gasket (part# RK10040-CHG).

Remember, the water belongs to everyone. Please ride responsibly and respect the environment!

Technical Support

For answers to questions regarding installation or trouble shooting RIVA Performance Products contact: RIVA Technical Support directly at (954) 247-0705 or by e-mail at <u>tech_support@rivaracing.com</u>.

Warranty Disclaimer

Due to the nature of performance applications, this product is sold without any express warranty or any implied warranty of merchantability or fitness or a particular purpose. RIVA Racing shall not, under any circumstances, be liable for any special, incidental or consequential damages, including, person, party or property, but not limited to, damage, or loss of property or equipment, loss of profits or revenue, cost of purchased or replacement goods, or claims of customers of the purchase, which may arise and/or result from sale, installation or use of these parts. Installation of this part will void the motor manufacturer's warranty coverage.