



Kawasaki 800 SX-R Reed Spacer Kit

PART# - RK14080

APPLICATION: `03~05 800 SX-R

INSTALLATION INSTRUCTIONS

- 1. Remove wrist lanyard, turn fuel valve to "off" position and disconnect battery cables from battery.
- 2. Remove carburetors from intake manifold.
- Remove intake manifold.
- 4. Remove OE mounting studs from crankcase and discard.
- 5. Thoroughly clean intake manifold and crankcase mating surfaces. Take care not to allow foreign objects to enter crankcase. **NOTE: Use only non-residual cleaners.**
- 6. Install supplied intake manifold mounting studs into crankcase. **NOTE: Use blue Loc-tite on threads. Do not over tighten studs. Clean excess Loc-tite.**
- 7. Install one supplied reed spacer gasket onto each intake track. NOTE: Do not use sealant on gaskets.
- 8. Install one supplied reed spacer plate onto each intake track so widest side is at top. **NOTE: Do not use sealant on reed spacer plates.**
- 9. Install one supplied reed spacer gasket onto each intake track. NOTE: Do not use sealant on gaskets.
- 10. Install reed cage assemblies into intake tracks. NOTE: Do not use sealant on reed cage assemblies.
- 11. Install OE metal gaskets onto each reed cage assembly. NOTE: Do not use sealant on gaskets.
- 12. Install intake manifold. NOTE: Torque nuts to 8ft-lbs.
- 13. Install carburetors. Be sure fuel lines and throttle cable are properly secured.
- 14. Inspect engine compartment for tools, rags, and foreign objects.
- 15. Reconnect battery cables, turn fuel valve to "on" position and run craft on flush kit to ensure safe, normal operation.

Remember, the water belongs to everyone. Please ride responsibly!

Technical Support

For answers to questions regarding installation or trouble shooting RIVA Performance Products contact: RIVA Technical Support directly at (954) 247-0705 or by e-mail at tech_support@rivamotorsports.com

1-Year Limited Warranty

RIVA SX-R Reed Spacer Kits carry a 1-year limited warranty to the original purchaser. They are warranted to be free of defects in materials and workmanship under normal use and service. Customer modified components will be void of warranty. This warranty is limited to defects in the primary components only (reed spacer plates). Finish and/or wear marks in or on primary components are not covered under this warranty.

RIVA Racing's liability is expressly limited to the repair or replacement of the components contained within or associated with this kit. RIVA Racing agrees to repair or at RIVA's option, replace any defective unit without charge, if product is returned to RIVA Racing freight prepaid within the warranty period. Any equipment returned which, in RIVA's opinion, has been subjected to misuse, abuse, overheating or accident shall not be covered by this warranty.

RIVA Racing shall have no liability for special, incidental or consequential damages or injury to persons or property from any cause arising from the sale, installation or use of this product.

No other warranty, express or implied, including, but not limited to the implied warranties of merchantability and fitness for a particular purpose, applies. Various states do not allow for the limitation of incidental or consequential damages and therefore the above exclusion or limitation may not apply to you.

Warranty does not include the expenses related to freight or transportation of parts or compensation for any inconvenience or loss of use while being repaired. A copy of the original invoice must accompany all warranty claims.

Warranted replacement parts will be returned freight collect.

Word doc. RK14080 © H1 4/13/05