



1.8L Replacement Performance Air Filter

PART# RY13040-OE

We strongly recommend the use of a service manual to familiarize yourself with the various components and procedures involved with this installation. Please note that some of the original clamps, hoses and hardware removed in the disassembly process will be used in the installation process. These instructions have been written in step-by-step format and refer to illustrations. Read through instructions entirely before performing installation. Please follow these step-by-step instructions and illustrations carefully.


APPLICATION(S): Yamaha 1.8L PWC Engines

***** ALLOW ENGINE TO COOL COMPLETELY BEFORE PERFORMING INSTALLATION *****


- INSTALLATION INSTRUCTIONS -

Remove safety lanyard.

SHO/SVHO Models: Disconnect engine breather hose from supercharger air inlet hose. Remove supercharger air inlet hose.



HO Models: Disconnect engine breather hose from air inlet hose located between air box & throttle body. Remove air inlet hose.



Release air box clips (8 clips / 2 on each side) and remove air box lid with element.




Remove screws (3) securing OE air element to lid. Remove element. Discard element & screws.



Clean air box & lid of any foreign particles or debris.

Install Performance Air Filter onto air box lid. Ensure filter is seated in outer groove of lid. **Note:** Filter is directional. Make sure "RIVA RACING" logo is facing inside of lid. (RIVA RACING logo on exit side of filter)



With Performance Air Filter in place on lid, reinstall lid onto air box and secure air box clips (8).

Reinstall air inlet hose. **Do not over tighten clamps.**

Reinstall engine breather hose to air inlet hose.

Check bilge for tools, rags, etc. Run craft on a flush kit to check for proper operation.

***Remember, the water belongs to everyone.
Please ride responsibly and respect the environment!***

Technical Support

For answers to questions regarding installation or trouble shooting RIVA Performance Products contact:
RIVA Technical Support directly at (954) 247-0705 or by e-mail at tech_support@rivamotorsports.com.

Limited Warranty

RIVA Replacement Performance Air Filters carry a 1 year limited warranty to the original purchaser. They are warranted to be free of defects in materials and workmanship under normal use and service. Customer modified components will be void of warranty. This warranty is limited to defects in the primary components only. Finish and/or wear marks in or on primary components are not covered under this warranty.

RIVA Racing's liability is expressly limited to the repair or replacement of the components contained within or associated with this kit. RIVA Racing agrees to repair or at RIVA's option, replace any defective unit without charge, if product is returned to RIVA Racing freight prepaid within the warranty period. Any equipment returned which, in RIVA's opinion, has been subjected to misuse, abuse, overheating or accident shall not be covered by this warranty.

RIVA Racing shall have no liability for special, incidental or consequential damages or injury to persons or property from any cause arising from the sale, installation or use of this product.

No other warranty, express or implied, including, but not limited to the implied warranties of merchantability and fitness for a particular purpose, applies. Various states do not allow for the limitation of incidental or consequential damages and therefore the above exclusion or limitation may not apply to you.

Warranty does not include the expenses related to freight or transportation of parts or compensation for any inconvenience or loss of use while being repaired. A copy of the original invoice and a Return Authorization Number (RA#) must accompany all warranty claims.

Warranted replacement parts will be returned freight collect.