



# Pro-Series Fuel Injection Kit PART# - RS12090-I-KIT-75

APPLICATION(S): Sea-Doo iControl models equipped with Bosch ECU's.

## - INSTALLATION INSTRUCTIONS -

Installation of this RIVA Performance Product requires the use of an Aftermarket ECU and/or Fuel Pressure Regulator Kit. Failure to do so could result in engine damage.

### \* \* \* NO SMOKING. ALLOW ENGINE TO COOL COMPLETELY \* \* \*

- 1. Remove D.E.S.S. lanyard and disconnect battery cables. NOTE: Negative (black) first. Positive (red) second.
- 2. Remove oil level dipstick. Remove plastic valve cover.
- 3. Remove Torx screws (2) securing fuel rail to intake manifold. (see illustration #1)
- 4. Carefully remove OE fuel injectors from intake manifold. If engine was previously run disconnect fuel line to fuel rail and drain fuel rail. NOTE: Fuel rail is under pressure. Cover connection with a shop rag when disconnecting.
- 5. Disconnect electrical connectors from OE fuel injectors. (see illustration #2)
- 6. Carefully remove metal clips securing OE fuel injectors to fuel rail. (see illustration #3)
- 7. Carefully remove OE fuel injectors from fuel rail.
- 8. Install supplied billet spacers into fuel rail. Install RIVA Pro-Series Fuel Injectors into billet spacers. (see illustration #4) **NOTE: Coat o-rings with motor oil.**
- 9. Install supplied jumper wires onto fuel injectors. (see illustration #5)
- 10. Install fuel injectors into intake manifold. Secure fuel rail to intake manifold using OE Torx screws. (see illustration #6) **NOTE: Use BLUE Loctite. Do not over tighten bolts.**
- 11. Connect jumper wires to stock electrical connectors. (see illustration #6)
- 12. Replace plastic valve cover. Replace oil level dipstick.
- 13. Reconnect battery cables. NOTE: Positive (red) first. Negative (black) second.
- 14. Run craft on flush kit prior to water testing.

# Remember, the water belongs to everyone. Please ride responsibly!

#### **Technical Support**

For answers to questions regarding installation or trouble shooting RIVA Performance Products contact: RIVA Technical Support directly at (954) 247-0705 or by e-mail at <a href="mailto:tech\_support@rivamotorsports.com">tech\_support@rivamotorsports.com</a>

NOTE: Due to the nature and intended use of this product we do not offer warranty coverage.











