



## **Mirror Block-off Kit** **PART# - RY5-FZ-MB**

**APPLICATION(S):** Yamaha FZR & FZS

### **- INSTALLATION INSTRUCTIONS -**

1. Open front storage hatch and remove the two M12 nuts securing left and right mirror assemblies to hood.
2. Carefully remove rubber mounting pads from mirror assemblies. **NOTE:** Pads are marked L and R on back side. This is important since they will be used on opposite sides of watercraft for installation of RIVA Mirror Block-off's. (see illustration #1)
3. Using the rubber mounting pad marked R, locate the **left hand side** block-off and install onto the pad. The block-off will fit perfectly into the recessed area of the mounting pad. (see illustration #2)
4. Locate the supplied Delrin spacers and install into the left hand side mounting holes from the inside of the hood. (see illustration #3) **NOTE:** The spacers are two different sizes. The small spacer should be used in the front hole and the large spacer in the rear hole. Position block-off and mounting pad over holes and secure using supplied M6x 25mm hex bolts, M6 lock washers and M6 flat washers. **NOTE: Apply blue Loc-tite to the bolts and tighten down until the bolt bottoms out on the Delrin spacer. Do not over tighten bolts.**
5. Complete installation by repeating the process on right hand side. (see illustration #4)

***Remember, the water belongs to everyone.  
Please ride responsibly and respect the environment!***

### **Technical Support**

For answers to questions regarding installation or trouble shooting RIVA Performance Products contact:  
RIVA Technical Support directly at (954) 247-0705 or by e-mail at [tech\\_support@rivamotorsports.com](mailto:tech_support@rivamotorsports.com).

### **Limited Warranty**

RIVA Mirror Block-off Kits carry a 6-month limited warranty to the original purchaser. They are warranted to be free of defects in materials and workmanship under normal use and service. Customer modified components will be void of warranty. This warranty is limited to defects in the primary components only. Finish and/or wear marks in or on primary components are not covered under this warranty.

RIVA Racing's liability is expressly limited to the repair or replacement of the components contained within or associated with this kit. RIVA Racing agrees to repair or at RIVA's option, replace any defective unit without charge, if product is returned to RIVA Racing freight prepaid within the warranty period. Any equipment returned which, in RIVA's opinion, has been subjected to misuse, abuse, overheating or accident shall not be covered by this warranty.

RIVA Racing shall have no liability for special, incidental or consequential damages or injury to persons or property from any cause arising from the sale, installation or use of this product.

No other warranty, express or implied, including, but not limited to the implied warranties of merchantability and fitness for a particular purpose, applies. Various states do not allow for the limitation of incidental or consequential damages and therefore the above exclusion or limitation may not apply to you.

Warranty does not include the expenses related to freight or transportation of parts or compensation for any inconvenience or loss of use while being repaired. A copy of the original invoice and a Return Authorization Number (RA#) must accompany all warranty claims.

Warranted replacement parts will be returned freight collect.

## - Illustration Images -



Illustration #1



Illustration #2



Illustration #3



Illustration #4