



Pro-Series Sponson Kit PART# RK26090

APPLICATION(S): Kawasaki Ultra 310/300/260/250X/LX

- INSTALLATION INSTRUCTIONS -

- 1. Remove the four socket head cap bolts securing stock sponsons to hull. (see illustration #1) Remove stock sponsons and discard.
- 2. Clean hull using a non-residual cleaner such as PJ1 Supercleaner.
- 3. Apply a thin coat of silicone sealant (for use below waterline) to back side of supplied sponson backing plates. **TIP: Perform steps 3~5 on one side at a time!**
- 4. Install backing plate over brass inserts in hull. NOTE: Backing plates fit one way only. (see illustration #2) Secure backing plate to hull using supplied socket head cap screws and flat washers. Remove excess silicone after tightening bolts. NOTE: Apply red Loc-tite to threads. Do not over tighten bolts.
- 5. Install RIVA Pro-Series Sponson Fins using supplied Phillips head screws and M6 wavy washers. (see illustration #3) NOTE: Apply blue Loc-tite to threads. Do not over tighten screws.

NOTE: For the purpose of these instructions the sponson fins were installed in the lower- and forward-most position to provide the most influence. This is the most "aggressive" configuration. Moving the sponsons up and/or rearward will lessen their influence. This is the least "aggressive" configuration. Be sure to reapply Loc-tite each time you adjust sponson blades.

Remember, the water belongs to everyone. Please ride responsibly!

Technical Support

For answers to questions regarding installation or trouble shooting RIVA Performance Products contact: RIVA Technical Support directly at (954) 247-0705 or by e-mail at tech_support@rivamotorsports.com

Limited Warranty

RIVA Pro-Series Sponsons carry a 30-day limited warranty to the original purchaser. They are warranted to be free of defects in materials and workmanship under normal use and service. Customer modified components will be void of warranty. This warranty is limited to defects in the primary components only. Finish and/or wear marks in or on primary components are not covered under this warranty.

RIVA Racing's liability is expressly limited to the repair or replacement of the components contained within or associated with this kit. RIVA Racing agrees to repair or at RIVA's option, replace any defective unit without charge, if product is returned to RIVA Racing freight prepaid within the warranty period. Any equipment returned which, in RIVA's opinion, has been subjected to misuse, abuse, overheating or accident shall not be covered by this warranty.

RIVA Racing shall have no liability for special, incidental or consequential damages or injury to persons or property from any cause arising from the sale, installation or use of this product.

No other warranty, express or implied, including, but not limited to the implied warranties of merchantability and fitness for a particular purpose, applies. Various states do not allow for the limitation of incidental or consequential damages and therefore the above exclusion or limitation may not apply to you.

Warranty does not include the expenses related to freight or transportation of parts or compensation for any inconvenience or loss of use while being repaired. A copy of the original invoice must accompany all warranty claims.

Warranted replacement parts will be returned freight collect.

Word doc. RK26090 © H1 12/16/13

- INSTALLATION IMAGES -



Illustration #1



Illustration #2



Illustration #3