



GP PERFORMANCE RIDE PLATE

PART# - RY 21017-1RF

INSTALLATION INSTRUCTIONS

APPLICATION: 1997-99 GP760/1200 & 1998-2000 GP800.

NOTE: This is a Riva Yamaha racing component. It is designed for competition use only. Failures caused by the use of this component are not covered by the Yamaha limited warranty.

1. Remove the four O.E. 8mm bolts holding ride plate in place.
2. Install the RIVA GP Performance Ride Plate using the four O.E. 8mm bolts and torque to 17Nm (1.7m/kg • 12ft/lbs).
NOTE: Use Loctite 572 on bolts. DO NOT OVER TORQUE.

This ride plate was designed to be tunable as to how much influence it has on the crafts handling characteristics. This is done by installing the included washers between the two rear mounts of the ride plate and the hulls mounting surface.

For the most speed, install the ride plate flush against the hull.

For more handling, install one washer at a time between each of the two rear ride plate mounts and the hull, thus shimming the end of the ride plate down. This will push the nose of the craft down slightly providing more handling. If you are still experiencing handling problems you may need to add more washers to shim the ride plate down further.

It is recommended that the ride plate is not shimmed so the rear edge is lower than level with the planing surface of the hull. This can be determined by placing a long straight edge on either side of the pump and back past the ride plate.

IMPORTANT: Technical Support

For answers to questions regarding installation or trouble shooting Riva Yamaha Ride Plate contact:
Riva Yamaha Tech Line @ (954) 247-0705 or online at tech_support@rivayamaha.com
Or you're local Yamaha Dealer

Riva Yamaha Limited 1-Year Warranty

Riva Yamaha Ride Plates carry a one-year limited warranty to the original purchaser. They are warranted to be free of defects in materials and workmanship under normal use and service. Customer modified components will be void of warranty. This warranty is limited to defects in the primary aluminum component only. The powder-coated finish is not covered under this warranty.

Riva Yamaha's liability is expressly limited to the repair or replacement of the aluminum components contained within or associated with this ride plate. Riva Yamaha agrees to repair or at Riva Yamaha's option, replace any defective unit without charge, if product is returned to Riva Yamaha freight prepaid within the warranty period. Any equipment returned which, in Riva Yamaha's opinion, has been subjected to misuse, abuse, overheating or accident shall not be covered by this warranty.

Riva Yamaha shall have no liability for special, incidental or consequential damages or injury to persons or property from any cause arising from the sale, installation or use of this product.

No other warranty, express or implied, including, but not limited to the implied warranties of merchantability and fitness for a particular purpose, applies. Various states do not allow for the limitation of incidental or consequential damages and therefore the above exclusion or limitation may not apply to you.

Warranty does not include the expenses related to freight or transportation of parts or compensation for any inconvenience or loss of use while being repaired. A copy of the original invoice must accompany all warranty claims.

Warranted replacement parts will be returned freight collect.

Remember the water belongs to everyone! Please ride responsibly!