



## FZ Performance Ride Plate PART# - RY21050

APPLICATION(S): Yamaha FZR & FZS Models

### - INSTALLATION INSTRUCTIONS -

- 1. Remove the four screws securing speedo sensor to stock ride plate.
- 2. Remove the four bolts securing stock ride plate to hull.
- Transfer the two stainless steel spacer plates from the stock ride plate to the supplied ride plate. Do not discard spacer plates.
- 4. Install supplied ride plate, with stock spacer plates, and secure with stock bolts. NOTE: Apply blue Loctite to bolts. Torque to 12.5 lb•f / 17 N•m.
- 5. Replace speedo sensor. NOTE: Apply blue Loctite to bolts. Torque to 3.0 lbef / 4.0 Nem.

This ride plate was designed to be tunable as to how much influence it has on the crafts handling characteristics. This is done by installing the included washers between the two rear mounts of the ride plate and the stock spacer plates. **Do not install washers at front two mounting locations or between hull and stock spacer plates.** 

For the most speed install the ride plate, with stock spacer plates, flush against hull. Do not remove spacer plates.

It is recommended that the ride plate is not shimmed so much that the rear edge is lower than level with the hull's planing surface. This can be determined by placing a long metal straight edge on either side of the pump and back past the ride plate.

# Remember, the water belongs to everyone. Please ride responsibly and respect the environment!

### **Technical Support**

For answers to questions regarding installation or trouble shooting RIVA Performance Products contact: RIVA Technical Support directly at (954) 247-0705 or by e-mail at <a href="mailto:tech-support@rivamotorsports.com">tech-support@rivamotorsports.com</a>.

#### **Limited Warranty**

RIVA Ride Plates carry a 1-year limited warranty to the original purchaser. They are warranted to be free of defects in materials and workmanship under normal use and service. Customer modified components will be void of warranty. This warranty is limited to defects in the primary components only. Finish and/or wear marks in or on primary components are not covered under this warranty.

RIVA Racing's liability is expressly limited to the repair or replacement of the components contained within or associated with this kit. RIVA Racing agrees to repair or at RIVA's option, replace any defective unit without charge, if product is returned to RIVA Racing freight prepaid within the warranty period. Any equipment returned which, in RIVA's opinion, has been subjected to misuse, abuse, overheating or accident shall not be covered by this warranty.

RIVA Racing shall have no liability for special, incidental or consequential damages or injury to persons or property from any cause arising from the sale, installation or use of this product

No other warranty, express or implied, including, but not limited to the implied warranties of merchantability and fitness for a particular purpose, applies. Various states do not allow for the limitation of incidental or consequential damages and therefore the above exclusion or limitation may not apply to you.

Warranty does not include the expenses related to freight or transportation of parts or compensation for any inconvenience or loss of use while being repaired. A copy of the original invoice and a Return Authorization Number (RA#) must accompany all warranty claims.

Warranted replacement parts will be returned freight collect.

Word doc. RY21050 © H1 6/9/10