



2021+ SuperJet Handlepole Spring

RY10130

Applications: 2021+ Yamaha SuperJet

Approximate Installation Time: .5 Hr.

Recommended Specialty Tools: N/A

Required Materials: marine grease, blue Loctite

We strongly recommend the use of a service manual to familiarize yourself with the various components and procedures involved with this installation. Please note that some of the original hardware removed in the disassembly process will be used in the installation process. These instructions have been written in step-by-step format and refer to illustrations. Read through instructions entirely before performing installation. Please follow these step-by-step instructions and illustrations carefully.



***** ALLOW ENGINE TO COOL COMPLETELY BEFORE PERFORMING INSTALLATION *****

***** NO SMOKING *** NO SMOKING *** NO SMOKING *****

Caution: Whenever using electric or battery operated tools inside the hull be sure it is well ventilated and no fumes are present. Failure to do so could result in a fire, or explosion and serious personal injury or death.




Figure 1
Remove engine hatch.
Remove nut and washer from handlepole bolt.
Unscrew bolt from bracket.




Figure 2
Pull bolt out of right side bracket just enough to remove OEM spring.
Note: Do not remove bolt from right side handlepole bushing.




Figure 3

Apply marine grease to bolt shaft.




Figure 4

Insert "tail" of supplied spring into hole in bottom of bracket.

While pushing spring toward front of craft, slide bolt through spring and left side handlepole bushing.




Figure 5

Apply blue Loctite to threads in bracket and nut.

Align bolt with bracket hole and screw through bracket.

Tighten to 11 ft•lb (15 Nm).

Test handlepole for free movement.




Figure 6

Reinstall OEM Washer and nut. Tighten to 50 ft•lb (70 Nm).

Test handlepole for free movement.

Reinstall engine hatch.

***Remember, the water belongs to everyone.
Please ride responsibly and respect the environment!***

Technical Support

For answers to questions regarding installation or trouble shooting RIVA Performance Products contact:
RIVA Technical Support directly at (954) 247-0705 or by e-mail at tech_support@rivaracing.com.

Limited Warranty

RIVA handlepole springs carry a 90 day limited warranty to the original purchaser. They are warranted to be free of defects in materials and workmanship under normal use and service. Customer modified components will be void of warranty. This warranty is limited to defects in the primary components only. Finish and/or wear marks in or on primary components are not covered under this warranty.

RIVA Racing's liability is expressly limited to the repair or replacement of the components contained within or associated with this kit. RIVA Racing agrees to repair or at RIVA's option, replace any defective unit without charge, if product is returned to RIVA Racing freight prepaid within the warranty period. Any equipment returned which, in RIVA's opinion, has been subjected to misuse, abuse, overheating or accident shall not be covered by this warranty.

RIVA Racing shall have no liability for special, incidental or consequential damages or injury to persons or property from any cause arising from the sale, installation or use of this product.

No other warranty, express or implied, including, but not limited to the implied warranties of merchantability and fitness for a particular purpose, applies. Various states do not allow for the limitation of incidental or consequential damages and therefore the above exclusion or limitation may not apply to you.

Warranty does not include the expenses related to freight or transportation of parts or compensation for any inconvenience or loss of use while being repaired. A copy of the original invoice and a Return Authorization Number (RA#) must accompany all warranty claims.