



RIVA RACING
PERFORMANCE PRODUCTS & ACCESSORIES

Yamaha GPR Performance Ride Plate

RY21013



- INSTALLATION INSTRUCTIONS -

Remove screws (4) securing speed sensor to ride plate.

NOTE: Do not use an impact tool. Carefully warm screws, but do not overheat. Speed Sensor housing is made of plastic.

Remove bolts (4) securing ride plate to hull. **NOTE: Do not use an impact tool. If bolts are difficult to loosen apply heat directly to bolthead.**

Install RIVA Performance Ride Plate and secure with stock hardware. **NOTE: Verify ride plate is aligned properly. Apply blue Loctite to bolts. Torque bolts to 12 ft•lbs (17 N•m / 1.7 kgf). Do not overtighten.**

Secure speed sensor to ride plate with stock screws. **NOTE: Apply blue Loctite to screws. Torque screws to 2.7 ft•lbs (3.7 N•m / 0.37 kgf). Do not overtighten.**

GET THE LATEST UPDATES!

Prior to installation, go to the RIVA Racing online Instruction Library to download the latest version of these instructions:

<https://rivaracing.com/instructions>

Applications: 2000~08 Yamaha GPR 800/1200/1300

Approximate Installation Time: 0.5hrs

Recommended Specialty Tools: **Part #**

N/A N/A

Required Materials: **Part #**

Blue Loctite N/A

Remember, the water belongs to everyone.

Please ride responsibly and respect the environment!

Technical Support

For answers to questions regarding installation or trouble shooting RIVA Performance Products contact:

RIVA Technical Support directly at (954) 247-0705 or by e-mail at tech_support@rivaracing.com.

Limited Warranty

RIVA Ride Plates carry a 1-year limited warranty to the original purchaser. They are warranted to be free of defects in materials and workmanship under normal use and service. Customer modified components will be void of warranty. This warranty is limited to defects in the primary components only. Finish and/or wear marks in or on primary components are not covered under this warranty.

RIVA Racing's liability is expressly limited to the repair or replacement of the components contained within or associated with this kit. RIVA Racing agrees to repair or at RIVA's option, replace any defective unit without charge, if product is returned to RIVA Racing freight prepaid within the warranty period. Any equipment returned which, in RIVA's opinion, has been subjected to misuse, abuse, overheating or accident shall not be covered by this warranty.

RIVA Racing shall have no liability for special, incidental or consequential damages or injury to persons or property from any cause arising from the sale, installation or use of this product.

No other warranty, express or implied, including, but not limited to the implied warranties of merchantability and fitness for a particular purpose, applies. Various states do not allow for the limitation of incidental or consequential damages and therefore the above exclusion or limitation may not apply to you.

Warranty does not include the expenses related to freight or transportation of parts or compensation for any inconvenience or loss of use while being repaired. A copy of the original invoice and a Return Authorization Number (RA#) must accompany all warranty claims.

Warranted replacement parts will be returned freight collect.